


balkstaal

breedflensbalken, HEB

leveringsvoorwaarden: NEN-EN 10025-1 en -2
 toleranties: NEN-EN 10034; DIN 1025/2
 max. handelslengte: 28 m



profiel nr.	G ₈ kg/m	A mm ²	h mm	b mm	t _w mm	t _f mm	A _L m ² /m	I _y x10 ⁴ mm ⁴	W _{y,rel} x10 ³ mm ³	I _z x10 ⁴ mm ⁴	W _{z,rel} x10 ³ mm ³	profiel nr.
100	20,8	2604	100	100	6	10	0,567	450	89,9	167	33,5	100
120	27,2	3401	120	120	6,5	11	0,686	864	144	318	52,9	120
140	34,4	4296	140	140	7	12	0,805	1509	216	550	78,5	140
160	43,4	5425	160	160	8	13	0,918	2492	312	889	111	160
180	52,2	6525	180	180	8,5	14	1,04	3831	426	1363	151	180
200	62,5	7808	200	200	9	15	1,15	5696	570	2003	200	200
220	72,8	9104	220	220	9,5	16	1,27	8091	736	2843	258	220
240	84,8	10599	240	240	10	17	1,38	11259	938	3923	327	240
260	94,8	11844	260	260	10	17,5	1,50	14919	1148	5135	395	260
280	105	13136	280	280	10,5	18	1,62	19270	1376	6595	471	280
300	119	14908	300	300	11	19	1,73	25166	1678	8563	571	300
320	129	16134	320	300	11,5	20,5	1,77	30824	1926	9239	616	320
340	137	17090	340	300	12	21,5	1,81	36656	2156	9690	646	340
360	145	18063	360	300	12,5	22,5	1,85	43193	2400	10141	676	360
400	158	19778	400	300	13,5	24	1,93	57681	2884	10819	721	400
450	174	21798	450	300	14	26	2,03	79888	3551	11721	781	450
500	191	23864	500	300	14,5	28	2,12	107176	4287	12624	842	500
550	203	25406	550	300	15	29	2,22	136691	4971	13077	872	550
600	216	26996	600	300	15,5	30	2,32	171041	5701	13530	902	600
650	229	28634	650	300	16	31	2,42	210616	6480	13984	932	650
700	245	30638	700	300	17	32	2,52	256888	7340	14441	963	700
800	267	33418	800	300	17,5	33	2,71	359084	8977	14904	994	800
900	297	37128	900	300	18,5	35	2,91	494065	10979	15816	1054	900
1000	320	40005	1000	300	19	36	3,11	644748	12895	16276	1085	1000